

ENVIRONMENTAL PRODUCT DECLARATION


IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

JITA ICT CABLE PROTECTION PIPES (DW AND TRIPLE)



EPD HUB, HUB-2500 Publishing date 11 December 2024, last updated on 31 January 2025, valid until 11 December 2029.









GENERAL INFORMATION

MANUFACTURER

Manufacturer	Jita Oy
Address	Lakarintie 10, 34800 Virrat, Finland
Contact details	info@jita.fi
Website	www.jita.fi

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	-
Scope of the EPD	Cradle to gate with options, A4-A5, and modules C1-C4, D
EPD author	Dr. Qian Wang, Uponor Corporation
EPD verification	Independent verification of this EPD and data, according to ISO 14025: □ Internal verification ☑ External verification
EPD verifier	Magaly González Vázquez, as an authorized verifier acting for EPD Hub Limited

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	ICT Cable Protection Pipes (DW and Triple Cable Protection Pipes)
Additional labels	Range OD (outer diameter) 50 – 200 mm
Product reference	960105, 960106, 960107, 960108, 960109, 960110, 960118, 960119, 960129, 960139, 960159, 960169, 960408, 960409, 960518, 960519, 960520, 960521, 960607, 960608, 960609, 960610, 960611, 960709, 961104, 961106, 961107, 961108, 965510, 965511, 965708, 965709
Place of production	Jita Oy, Lakarintie 10, 34800 Virrat, Finland
Period for data	2022
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	-

One Click



ENVIRONMENTAL DATA SUMMARY

Declared unit	1 kg of pipe
Declared unit mass	1 kg
GWP-fossil, A1-A3 (kgCO2e)	2,18E+00
GWP-total, A1-A3 (kgCO2e)	2,18E+00
Secondary material, inputs (%)	105
Secondary material, outputs (%)	0
Total energy use, A1-A3 (kWh)	12.7
Total water use, A1-A3 (m3e)	0.09

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Jita is Finnish plastics industry company with almost half a century expertise. Our offering includes wide range of plastics solutions that are used for making living environment better. Whether the case is stormwater or network infra, or highly reliable wastewater treatment, we always deliver it – in sustainable way.

PRODUCT DESCRIPTION

Electricity, telecommunication, and fibre cables are going everywhere. Those cables need to be protected adequately to prevent damaging or cut off. Jita develops and manufactures solutions for the protection of low and high voltage cables and all kind of data transmission. This EPD covers two kinds of products within Jitel Cable Protection Pipes.





- 1) Cable protection pipes, double wall
- Pipes have a smooth inside layer and a corrugated outside layer.
- 6 m straight lengths or 50 m coils (dimensions OD 50 and 75 mm with ring stiffness SN8)
- Ring stiffness classification A = SN16 or B = SN8
- Pipes are available in dimensions: OD 50, 75, 110, 140, 160 and 200
- Raw material: polyethylene (PE) or polypropylene (PP)
- Colours: Mainly yellow and red, all other colours are also possible
- 2) Cable protection pipes, triple
- Pipes have a smooth inside layer and a smooth outside layer.
- 6 m straight lengths
- Ring stiffness classification A = SN16 and B = SN8
- Pipes are available in dimensions: OD 110, 140 and 160
- Raw material: polyethylene (PE)
- Colours: Mainly yellow and red, all other colours are also possible

Jitel cable protection pipes are classified according to standard SFS 5608, where A = SN16 and B = SN8. Ring stiffness is tested according to standard EN ISO 9969.

Further information can be found at www.jita.fi.





PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	-	-
Minerals	-	-
Fossil materials	100	-
Bio-based materials	-	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C

Biogenic carbon content in packaging, kg C 0.00002

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 kg of pipe
Mass per declared unit	1 kg
Functional unit	-
Reference service life	-

-

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).





PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

	rodu stage			mbly ige			U	lse stag	e			En	d of l	ife sta	age	s	Beyond the system boundaries					
A1	A2	A3	A4	A5	B1	B2	C1	C2	C3	C4		D										
x	x	x	MND	MND	MND	MND	MND	MND	MND	MND	MND	x	x	x	x	x						
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling				

Modules not declared = MND. Modules not relevant = MNR.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw material used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The production method is a pipe extrusion.

The different stages for the manufacturing process are:

- Material conveying
- Extrusion (melting and processing of material)
- Pipe profile corrugation
- Cooling
- [Coiling if needed]



- Cutting
- Socketing
- Packing



The finished straight lengths products are packed on a wooden U-frame with a wooden lath on top of it. The amount of pipes on a frame differs depending on the pipe diameter. The wooden frame has a nail plate on the edge to strengthen the structure as well as plastic or steel band around to tighten the package.

TRANSPORT AND INSTALLATION (A4-A5)

The transportation distance is defined according to the PCR. The average distance of transportation from the production plant to the installation site is based on the actual sales average figures of the company in the local markets. The installation scenarios in Jita's infrastructure product EPDs are based on TEPPFA's (The European Plastic Pipe and Fittings Association) industry averaged EPDs. These documents and their background reports include industry consensus estimates of the resource use, emissions and affluents of typical European installations; these parameters have been used as input for the Uponor EPD modelling. Environmental impacts from installation include standardized energy and installation tools, waste packaging materials and release of biogenic carbon dioxide from wood pallets. Reference: https://www.teppfa.eu/sustainability/environmental-footprint/epd/

PRODUCT USE AND MAINTENANCE (B1-B7)

This EPD does not cover the use phase. Air, soil, and water impacts during the use phase have not been studied.

CA Created with One Click LCA



PRODUCT END OF LIFE (C1-C4, D)

Since the consumption of energy and natural resources is negligible for disassembling of the end-of-life product, the impacts of demolition are assumed negligible (C1). After ca 100 years of service life 5 % of the end-of-life product is assumed to be sent to the closest treatment facilities (C2). The collected 5 % from the demolition site is sent to recycling (C3), whereas the remaining 95 % is left inert under the ground (C4). Due to the recycling of PE or PP, the end-of-life product is converted into recycled PE or PP (D).

LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1 % of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:



Data type	Allocation
Raw materials	No allocation
Packaging materials	Allocated by mass or volume
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	-

This EPD is product and factory specific and does not contain average calculations.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent and One Click LCA databases were used as sources of environmental d





ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO₂e	2,24E-01	1,06E-02	1,95E+00	2,18E+00	1,32E-01	9,17E-03	MND	2,67E-06	8,83E-02	8,67E-02	-1,31E-02	-2,46E-03						
GWP – fossil	kg CO₂e	2,02E-01	1,06E-02	1,97E+00	2,18E+00	1,32E-01	9,16E-03	MND	2,66E-06	8,83E-02	8,78E-02	7,25E-03	-2,46E-03						
GWP – biogenic	kg CO₂e	2,14E-02	0,00E+00	-2,50E-02	-3,52E-03	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	-1,07E-03	-2,04E-02	0,00E+00						
GWP – LULUC	kg CO₂e	3,32E-04	3,91E-06	2,45E-03	2,78E-03	4,41E-05	1,05E-05	MND	8,74E-09	7,95E-07	6,22E-07	6,15E-06	-1,63E-06						
Ozone depletion pot.	kg CFC-	1,90E-08	2,44E-09	2,14E-07	2,36E-07	3,06E-08	6,98E-10	MND	1,77E-13	3,38E-10	2,30E-10	1,95E-09	-1,31E-10						
Acidification potential	mol H⁺e	1,09E-03	4,49E-05	4,07E-02	4,19E-02	5,55E-04	4,60E-05	MND	3,24E-08	1,84E-05	1,64E-05	5,44E-05	-1,90E-05						
EP-freshwater ²⁾	kg Pe	1,46E-05	8,68E-08	3,37E-04	3,52E-04	2,16E-06	4,88E-07	MND	1,89E-10	1,91E-08	1,53E-08	1,06E-07	-1,36E-07						
EP-marine	kg Ne	2,41E-04	1,33E-05	3,79E-02	3,81E-02	1,66E-04	8,31E-06	MND	3,64E-09	8,26E-06	7,67E-06	1,89E-05	-2,07E-06						
EP-terrestrial	mol Ne	2,43E-03	1,47E-04	1,73E-01	1,75E-01	1,83E-03	8,50E-05	MND	4,18E-08	8,51E-05	7,86E-05	2,07E-04	-2,43E-05						
POCP ("smog") ³)	kg NMVOC	6,80E-04	4,71E-05	6,92E-03	7,65E-03	5,88E-04	2,52E-05	MND	1,39E-08	2,56E-05	2,35E-05	5,96E-05	-6,79E-06						
ADP-minerals & metals ⁴)	kg Sbe	1,89E-06	2,48E-08	1,44E-05	1,63E-05	1,26E-06	1,45E-07	MND	5,80E-10	6,02E-09	4,92E-09	2,53E-08	-1,78E-09						
ADP-fossil resources	MJ	3,60E+00	1,59E-01	1,70E+01	2,07E+01	2,01E+00	1,30E-01	MND	2,99E-05	2,58E-02	1,87E-02	1,44E-01	-2,97E-02						
Water use ⁵⁾	m³e depr.	8,25E-02	7,12E-04	3,75E+00	3,83E+00	8,23E-03	3,73E-03	MND	1,14E-06	2,46E-03	2,43E-03	8,86E-04	-2,56E-04						

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.





ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Particulate matter	Incidenc	1,19E-08	1,22E-09	2,79E-07	2,92E-07	1,36E-08	4,77E-10	MND	2,82E-13	3,85E-10	3,31E-10	1,04E-09	-1,65E-10						
Ionizing radiation ⁶⁾	kBq	7,62E-02	7,58E-04	9,35E-02	1,70E-01	9,18E-03	1,79E-03	MND	1,66E-07	1,05E-04	7,16E-05	7,69E-04	-3,65E-04						
Ecotoxicity (freshwater)	CTUe	5,77E+00	1,43E-01	7,97E+01	8,56E+01	1,67E+00	2,49E-01	MND	2,56E-04	8,85E-02	8,22E-02	1,13E-01	-5,43E-02						
Human toxicity,	CTUh	1,34E-10	3,52E-12	2,28E-09	2,41E-09	4,19E-11	1,00E-10	MND	1,33E-14	1,37E-11	1,35E-11	4,85E-12	-6,56E-13						
Human tox. non-	CTUh	3,31E-09	1,42E-10	1,73E-07	1,77E-07	1,81E-09	1,72E-10	MND	3,48E-13	1,73E-10	1,67E-10	9,06E-11	-2,00E-11						
SQP ⁷⁾	-	1,64E+00	1,83E-01	1,74E+02	1,76E+02	2,68E+00	5,77E-02	MND	3,08E-05	2,76E-02	1,95E-02	2,81E-01	-1,82E-02						

6) EN 15804+A2 disclaimer for lonizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Renew. PER as energy ⁸⁾	MJ	5,55E-01	1,79E-03	2,43E+01	2,49E+01	2,40E-02	2,22E-02	MND	3,90E-04	4,23E-04	3,44E-04	2,92E-03	-5,55E-03						
Renew. PER as material	MJ	0,00E+00	0,00E+00	2,34E+01	2,34E+01	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Total use of renew. PER	MJ	5,55E-01	1,79E-03	4,77E+01	4,83E+01	2,40E-02	2,22E-02	MND	3,90E-04	4,23E-04	3,44E-04	2,92E-03	-5,55E-03						
Non-re. PER as energy	MJ	3,59E+00	1,59E-01	1,70E+01	2,07E+01	2,01E+00	1,30E-01	MND	3,00E-05	2,58E-02	1,87E-02	1,44E-01	-2,97E-02						
Non-re. PER as material	MJ	2,69E+01	0,00E+00	0,00E+00	2,69E+01	0,00E+00	0,00E+00	MND	0,00E+00	2,12E+00	2,12E+00	0,00E+00	1,53E-16						
Total use of non-re. PER	MJ	3,05E+01	1,59E-01	1,70E+01	4,76E+01	2,01E+00	1,30E-01	MND	3,00E-05	2,15E+00	2,14E+00	1,44E-01	-2,97E-02						
Secondary materials	kg	1,05E+00	4,42E-05	1,21E-02	1,06E+00	2,79E-04	5,05E-04	MND	1,72E-07	1,76E-05	1,56E-05	5,80E-05	-1,71E-06						
Renew. secondary fuels	MJ	2,07E-05	4,46E-07	1,48E-04	1,69E-04	2,81E-06	4,47E-06	MND	6,61E-10	1,49E-07	1,29E-07	1,55E-06	-1,39E-08						
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Use of net fresh water	m ³	2,54E-03	2,06E-05	8,77E-02	9,03E-02	3,40E-04	4,71E-04	MND	3,14E-08	1,30E-05	1,21E-05	1,17E-04	-2,37E-05						

8) PER = Primary energy resources.






END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Hazardous waste	kg	1,30E-02	2,11E-04	2,21E-01	2,34E-01	2,31E-03	4,58E-03	MND	4,68E-07	6,10E-04	6,01E-04	2,78E-04	-1,98E-04						
Non-hazardous waste	kg	6,90E-01	3,47E-03	1,45E+00	2,15E+00	1,30E-01	2,04E-02	MND	9,49E-06	4,22E-02	4,20E-02	4,18E-01	-7,01E-03						
Radioactive waste	kg	2,43E-05	1,06E-06	5,56E-05	8,10E-05	1,36E-05	6,09E-07	MND	8,68E-11	1,33E-07	8,57E-08	9,06E-07	-1,34E-07						

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Components for re- use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Materials for recycling	kg	0,00E+00	0,00E+00	6,52E-02	6,52E-02	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,80E-03	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,38E-02	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						







ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	2,16E-01	1,05E-02	1,87E+00	2,09E+00	1,30E-01	9,18E-03	MND	2,59E-06	8,74E-02	8,69E-02	7,14E-03	-2,42E-03						
Ozone depletion Pot.	kg CFC- 11e	1,57E-08	1,93E-09	1,90E-07	2,07E-07	2,43E-08	5,91E-10	MND	1,56E-13	2,73E-10	1,88E-10	1,55E-09	-1,07E-10						
Acidification	kg SO₂e	8,95E-04	3,49E-05	2,34E-02	2,43E-02	3,51E-04	3,82E-05	MND	2,76E-08	1,32E-05	1,17E-05	4,11E-05	-1,63E-05						
Eutrophication	kg PO ₄ ³ e	6,61E-04	7,94E-06	2,26E-02	2,32E-02	7,67E-05	1,94E-05	MND	1,00E-08	2,57E-04	2,57E-04	1,24E-05	-4,49E-06						
POCP ("smog")	kg C_2H_4e	4,08E-05	1,36E-06	4,17E-04	4,59E-04	1,69E-05	1,87E-06	MND	1,45E-09	2,56E-06	2,50E-06	1,57E-06	-7,00E-07						
ADP-elements	kg Sbe	1,87E-06	2,41E-08	1,48E-05	1,67E-05	1,26E-06	1,44E-07	MND	5,78E-10	5,52E-09	4,45E-09	2,45E-08	-1,78E-09						
ADP-fossil	MJ	3,59E+00	1,59E-01	1,70E+01	2,07E+01	2,01E+00	1,30E-01	MND	2,99E-05	2,58E-02	1,87E-02	1,44E-01	-2,97E-02						

ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO₂e	2,02E-01	1,06E-02	1,97E+00	2,18E+00	1,32E-01	9,16E-03	MND	2,66E-06	8,83E-02	8,78E-02	7,25E-03	-2,46E-03						

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition, the characterisation factors for the flows - CH4 fossil, CH4 biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO2 is set to zero.







ENVIRONMENTAL IMPACTS – TRACI 2.1. / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Global Warming Pot.	kg CO₂e	2,12E-01	1,05E-02	1,94E+00	2,17E+00	1,30E-01	9,07E-03	MND	2,58E-06	8,69E-02	8,65E-02	7,13E-03	-2,40E-03						
Ozone Depletion	kg CFC-11e	1,57E-08	1,93E-09	1,90E-07	2,08E-07	2,83E-08	5,88E-10	MND	1,54E-13	2,73E-10	1,88E-10	1,55E-09	-1,04E-10						
Acidification	kg SO₂e	4,92E-02	2,13E-03	1,40E+00	1,45E+00	1,37E-02	2,03E-03	MND	1,36E-06	9,72E-04	8,78E-04	2,67E-03	-8,19E-04						
Eutrophication	kg Ne	7,10E-05	4,46E-06	3,73E-03	3,81E-03	6,14E-05	3,05E-06	MND	9,99E-10	4,42E-06	4,23E-06	4,52E-06	-2,87E-07						
POCP ("smog")	kg O₃e	5,53E-04	3,45E-05	8,05E-03	8,63E-03	5,41E-03	1,85E-05	MND	8,83E-09	2,23E-05	2,08E-05	4,88E-05	-5,41E-06						
ADP-fossil	MJ	2,25E-01	2,18E-02	2,10E+00	2,35E+00	2,81E-01	9,55E-03	MND	2,50E-06	3,46E-03	2,49E-03	1,91E-02	-1,56E-03						

ENVIRONMENTAL IMPACTS – BEPALINGSMETODE, NETHERLANDS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	С3	C4	D
Shadow price	€	5,14E-02	1,39E-03	6,48E-01	7,01E-01	1,58E-02	8,90E-03	MND	1,72E-06	2,43E-02	2,42E-02	1,22E-03	-4,20E-04						
Terrestrial ecotoxicity	DCB eq	2,95E-03	3,09E-05	1,05E+00	1,05E+00	2,93E-04	1,36E-04	MND	6,06E-08	3,04E-03	3,04E-03	2,30E-05	-9,50E-06						
Seawater ecotoxicity	DCB eq	9,81E+01	1,64E+00	3,58E+02	4,58E+02	1,86E+01	4,34E+00	MND	1,39E-03	2,58E+01	2,57E+01	1,50E+00	-1,22E+00						
Freshwater ecotoxicity	DCB eq	3,14E-03	1,82E-04	2,30E+00	2,30E+00	1,96E-03	1,84E-04	MND	1,40E-07	1,07E-02	1,07E-02	1,19E-04	-2,19E-05						
Human ecotoxicity	DCB eq	2,29E-01	5,20E-03	9,76E-01	1,21E+00	5,67E-02	8,51E-02	MND	1,37E-05	1,60E-01	1,60E-01	4,65E-03	-7,34E-04						
EEE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,09E-03	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
ETE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,87E-02	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
ADP Fossil Fuels	kg Sbe	1,73E-03	7,66E-05	8,16E-03	9,97E-03	9,67E-04	6,23E-05	MND	1,44E-08	1,24E-05	9,01E-06	6,93E-05	-1,43E-05						







VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.



I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Magaly González Vázquez, as an authorized verifier acting for EPD Hub Limited

Updated 31.01.2025



